

DEFAULT SYSTEM WATTAGE TABLES (courtesy of FocusonEnergy.com)

FOR COMMON CFL DOWNLIGHTS

Existing Lamp Configuration	Total System Wattage
(1) 13W CFL	16
(1) 18W CFL	23
(1) 26W CFL	31
(1) 32W CFL	35
(1) 42W CFL	46
(1) 36/39W 2G11 CFL	51
(1) 40W 2G11 CFL	48
(1) 55W 2G11 CFL	58
(2) 13W CFL	32
(2) 18 W CFL	46
(2) 26W CFL	62
(2) 32W CFL	70
(2) 42W CFL	92

FOR COMMON HID SYSTEMS

Existing Lamp Configuration	Total System Wattage
50W HID	65
70W HID	94
100W HID	126
150W HID	179
175W HID	210
250W HID	293
320W HID	356
400W HID	455
1,000W HID	1,079

FOR COMMON LINEAR FLUORESCENT SYSTEMS

	Existing Lamp Configuration	Total System Wattage
4-Foot Fixtures	1L F32 T8 Normal BF	33
	1L F34 T12	39
	1L F40 T12	39
	2L F32 T8 Normal BF	61
	2L FU32T8/6	55
	2L F34 T12	66
	2L F40 T12	79
	2L FU40T12	72
	3L F32 T8 Normal BF	91
	3L F34 T12	103
	3L F40 T12	124
	4L F54 T5H0	234
	4L F32 T8 Normal BF	120
	4L F32 T8 High BF	151
8-Foot Fixtures	4L F34 T12	136
	4L F40 T12	153
	6L F54 T5H0	355
	6L F32 T8 High BF	224
	8L F32 T8 High BF	291
	1L F96T8	61
	2L F96T8	107
	1L F96T12	69
	1L F96T12/HO	115
	2L F96T12	109
2L F96T12/HO	190	

